



## Elastomeric Rubber Casters – 45-ASE-0820-S



### Medium Duty

The blue elastic rubber wheel is floor protector and ideal for asphalt, concrete, wood and carpet surfaces. Elastic rubber mold to nylon center with 6203 precision ball bearing. The wheel is easy rolling, impact resistant and shock absorbing. 1/2" Inside diameter top hat bushings available. The wheel is ideal for industrial equipment, platform trucks, and rolling carts.

### Features

Design	Blue Elastomeric Rubber
Capacity	Up to 600 lbs.
Mounting Plate Size	4" X 4-1/4"
Bolt Hole Spacing	2-3/8" X 3-7/16"
Bolt Hole Spacing	2-5/8" X 3-5/8"
Mounting Bolt Diameter	1/2"






### Application

Food processing plant	Hand Trucks
Food service equipment	Service carts
Stock and maintenance carts	Dollies
Institutional service carts and equipment	



Available in Rigid

Available with brakes

 Wheel Diameter	 Wheel Width	 Capacity	 Wheel Type	 Overall Height
4"	2"	400	Elastomeric Rubber	5-1/8"
5"	2"	450	Elastomeric Rubber	6-1/8"
6"	2"	550	Elastomeric Rubber	7-1/4"
8"	2"	600	Elastomeric Rubber	9-3/16"