



Everlast Polyurethane Casters – MD/S118RX



Available in Stainless Steel and Zinc

Medium Duty

Quality, Life time, Wash ability, easy handling, and Material used in the production of these casters are selected and come exclusively from Italy. They are resistant to most cleaning agents and disinfectants and certified for food contact. The sealed precision ball races and bearings all regular cleaning without problems and do not require further maintenance. Our superior quality caster brackets are highly polished AISI 304 stainless, making them longer lasting and maintenance-free.

Features






Design	Stainless Steel Casters with Blue Everlast
Capacity	Up to 750 lbs.
Mounting Plate Size	3-11/32" X 4" or 4" X 4-1/4"
Bolt Hole Spacing	1-3/4" X 3" slotted to 2-3/8" X 3-7/16"
Bolt Hole Spacing	2-5/8" X 3" slotted to 3" X 3-5/8"
Mounting Bolt Diameter	3/8

Application

Food processing plant	Baking carts
Food service equipment	
Stock and maintenance carts	
Institutional service carts and equipment	

Call us on the different types of stem applications.



 Wheel Diameter	 Wheel Width	 Capacity	 Wheel Type	 Overall Height
3"	1-5/16"	330	Everlast Polyurethane	4-3/8"
4"	1-5/16"	400	Everlast Polyurethane	5-1/8"
5"	1-3/8"	475	Everlast Polyurethane	6-1/8"
5"	1-5/8"	600	Everlast Polyurethane	6-1/8"
6"	1-5/8"	650	Everlast Polyurethane	7-1/4"
8"	2"	750	Everlast Polyurethane	9-3/16"